Technical Data - Audi A3 Cabriolet 1.8 TFSI Attraction

depending on driving style and operating conditions

Model	Audi A3 Cabriolet 1.8 TFSI
Engine / electrics	
Engine type	Inline four-cylinder spark-ignition engine with petrol direct injection, exhaust turbo-charger with intercooler, 4 valves per cylinder, double overhead camshafts (DOHC)
Valve gear / number of valves per cylinder	Chain drive / roller cam followers / 4
Displacement in cc / bore x stroke in mm / compression	1798 / 82.5 x 84.1 / 9.6
Max. power output in kW (bhp) / at rpm	118 (160) / 5000 - 6200
Max. torque in Nm / at rpm	250 / 1500 - 4200
Mixture preparation	Direct injection/fully electronic with drive-by-wire throttle control, Bosch MED17
Exhaust emission control	Close-coupled ceramic primary catalytic converter and ceramic under floor catalytic converter with catalyst heating function via homogeneous split dual injection
Emissions class	EU 4
Alternator in A / battery in A/Ah	140 / 280 / 60
Drive / transmission	
	Front-wheel drive
Drive type Clutch	Two electro-hydraulically controlled
	multi-plate clutches in an oil bath
Gearbox type	6-speed S tronic dual-clutch gearbox with electro-hydraulic control
Gear ratio in 1st gear / 2nd gear	3.462 / 2.050
Gear ratio in 3rd gear / 4th gear	1.300 / 0.902
Gear ratio in 5th gear / 6th gear	0.914 / 0.756
Gear ratio in reverse gear	3.989
Final drive ratio	
Final drive ratio in 1st - 4th gear / 5th, 6th and reverse gear	4.375 / 3.333
Running gear / steering / brakes	
Front suspension	McPherson struts with lower wishbones, aluminium subframe, tubular anti-roll bar, track-stabilising steering roll radius
Rear suspension	Four-link rear suspension with separate spring/shock absorber arrangement, subframe, tubular anti-roll bar
Steering / steering ratio / turning circle in m (D102)	Electromechanical steering with speed-dependent
Steering / Steering ratio / turning circle in in (D102)	power assistance / 16.2 / approx. 10.7
Brake system, front/rear	Dual-circuit brake system with diagonal split. ESP with electronic brake-force distribution EBD, ABS; hydraulic brake assist; brake servo with dual-rate function,
Wheels / tyres	electronic differential lock EDL, front: ventilated discs, rear: discs Cast aluminium wheels, 7-spoke-design, 6.5Jx16", with 205/55 R16 tyres
	Cast autilificant wheels, 7-spoke-design, 0.55x10, with 205/351110 tyles
Performance / consumption / acoustics	
Top speed in km/h	218
Acceleration, 0-100 km/h in seconds	8,0
Fuel grade	Unleaded Super 95 RON
Fuel consumption: combined, I/100 km	7.6
CO ₂ mass emission, g/km	180
Standing / drive-past exterior noise level in dB (A)	80 / 73
Servicing / guarantee	
Servicing	12 months or 15,000 kms
Vehicle/paint/rust perforation guarantee	3 years with unlimited mileage / 3 years / 12 years
Weights / loads	
Unladen weight in kg / gross weight limit in kg	1455 / 1955
Axle load limit at front / rear in kg	1090 / 975
Trailer load limit at front / real linkg Trailer load limit on 8%/12% gradient, braked/unbraked in kg	1700 / 1400 / 750
Roof load limit in kg / permissible nose weight in kg	-/75
	1113
Capacities	
Cooling system capacity (incl. heating) in I	8.6
Engine oil capacity (incl. filter) in I	4.6
Fuel tank capacity in I	55
Body / dimensions	
Body type	Unitary steel body
Number of doors / seats	2 doors with additional side protection / 4 seats
Drag coefficient c / frontal area A in m	0,33 / 2,13
Length (L103)/ width excl. mirrors (W103)/ height (H100), mm	4238 / 1765 / 1424
Wheelbase (L101) / track at front/rear (W101/W102), mm	2578 / 1534 / 1507
Height of loading lip in mm (H195)	684
Luggage capacity in I, acc. to VDA block method (V211)	260/674
45 1 8 111 1 1 1 10	-